
COMPANY **INTRODUCTION**

Established in 1998, Ningbo DSW International Co.,ltd has specilized in manufactur

Certification



Contents

S F &

iezo

lec fron Sire

re w kup

Hor

Arm

p Alarm

CONTROL P NEL

RE

Smoke De

PIR SENSOR

EP

- Rat
- Op
- Ma
- Mi
- Re
- Ta
- Us

Value applying

Value applying at rated voltage



DSW®


DSW

DSW®

DSW®

The information contained herein os believed to be correct,but no guarantee for accura

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification



ES-79BU-20

◎ Voice Coil Impedance:	8 Ohm(at 1 KHz)
◎ Voice Coil Dimen(Dia.):	D25.4mm
◎ Magnet Size(Neo.):	60x32x10mm
◎ Rated Voltage:	12VDC
◎ Operating Volt	
◎	
◎	
◎	
◎	
◎	
◎	

Value applying at rated voltage



Value applying at rated voltage



Value applying at rated voltage

Value applying at rated voltage

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

EH-105

◎ Impedance:	80hm(at 1KHZ)
◎ Voice Coil:	Dia.25.4mm
◎ Magnet:	70*32*10mm(Dia.*dia*H)
◎ Reson Freq:Fo.	1.5KHz+/-10%
◎ Power Rating:	RMS:20W Peak:30W
◎ Min SPL:	95+/-3db(at 1 meter,2.83V,1000Hz)
◎ Housing:	ABS/Blank
◎ Oper.Temp.:	-20~+65℃
◎ Weight:	350+/-20g
◎ Remark:	70*32*10mm(Dia.*dia*H)



EH-104S

◎ Impedance:	6 Ohm at 1 Khz
◎ Voice Coil:	Dia. 25.4mm
◎ Magnet:	60*32*10 mm
◎ Reson Freq:	600 To 8 KHz
◎ Power Rating:	15 W(RMS)
◎ Min Spl:	95 dB/W/M Min
◎ Housing:	Black ABS Plastic
◎ Oper.Temp.:	20 ~ 60℃
◎ Weight:	360g
◎ Remark:	Real T Yoke



EH-202

◎ Impedance:	8 Ohm at 1 Khz
◎ Voice Coil:	Dia. 38 mm
◎ Magnet:	90 *45* 15 mm
◎ Reson Freq:	600 To 6 KHz
◎ Power Rating:	25 W RMS
◎ Min Spl:	96 dB/W/M (min)
◎ Housing:	ABS Plastic t
◎ Oper.Temp.:	20 T0 60
◎ W	
◎	

8 Ohm

Diameter

60

2

15

Wh


Val

EH 83


Impedance:

Voic

The information contained herein os believed to be correct,but no guarantee for accura



The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification



EAS-400LED(with LED)

Voice Coll Impedance:	8 Ohm
Input Voltage:	12 VDC
Oper Voltage:	6 To 15VDC
Min SPL:	115 dB at 12VDC/1m
Max Current:	1400 mA at 12VDC
Flash Rate:	15 +/-15 Per Minute
Strobe Len:	Acrylic Lens
Tone Nature:	Warble
Housing:	White ABS Plastic
weight:	1.2 Kg
Remark:	

EAS-2011

Value applying at rated voltage

DSW®

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

Value applying at rated voltage


The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

EBA-630











Value applying at rated voltage

Value applying at rated voltage

3-7

Value applying at rated v

Acrylic R

fe:

:

sions:

Remar

ed h

orrect nd
W ele

ntee for a
reseves th

s wi

DSM®

The information c

Value applying at

no guarantee for accuracy

TD.reseves the right to make


hout notification

Value applying at rated voltage

DSW®

The information contained herein os believed to be correct,but no guarantee for accura

Protecting the things you value most in life.



DSW®

DSM-236T/238T/2316T



Number of zones	DSM-236T:6 zones	DSM-238T:8 zones	DSM-2316T:16 zones
Supply Voltage	16.5VAC		
Total auxiliary power	400mA max		
Keypad’s Voltage	9.8-14.1VDC		
Keypad’s Current draw	Each LED keypad is 40mA		
Keypad type	LED keypad options		
Keypad operation	Up to 8 remote keypads		
Zone types	Alarm, alarm with walk-through, entry, entry with double delay 24-hour		
Zone timing	Entry delay-programmable from 10-300s,exit delay programmable from 10-150s		
Digital communicator			

Value applying at rated voltage

The information contained herein os believed to be correct,but no guarantee for accuracy completeness
DSW electronics LTD.reseves the right to make changes without notification


The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

Value applying at rated voltage

DSW®

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification



...information contained herein as believed to be correct but no guarantee for ...completeness
...make changes without notification

Power adaptor	185～230VAC（Input） 15V/800 mA（Output）
Build-in rechargeable battery	12V/1300 mAh
Static	≤40 mA /15V
Working Current	≤300mA /15V
Max 12V output current	≤100 mA
Wired siren	≤200mA /12V
Emitting frequency	433MHz/868MHz
Sensitivity	≥106dB
Emitting power	14±1 dB
Alarm dialing mode	DTMF
DTMF dialing frequency tolerance	< 1.5 %
CMS connection protocol	Ademco Contact ID
Environment	-5 ℃～+45 ℃
Humidity	< 85 %（Relative humidity）
Dimension	250×185×50mm



DSM-8824

Features

◎ Voice indication for operation，Easy to operate than before.
◎ Dual Serial Ports,access to wired and wireless keyboard.
◎ Support two-way communication, enable work with 8 dual-way wried keypad, 8 dual-way wireless keypad, 8 dual-way remote.
support GSM and TCP/IP protocol,network alarm settings.
◎ With 32 wireless zones, 8 wired zones.
◎ dopt bran new 16 bit MCU.
◎ Built-in video module,can view video

◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎

Value applying at rated voltage

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification

Power adaptor	input:185～230VAC output:12V/300mA
Rechargeable battery power apator	12V/500mAh
Build-in rechargeable battery	6V/500 mAh
Static	≤40mA /12V ≤30mA /6V
Working Current	≤300 mA /12V
Max 12V output current	≤100 mA
Recording time	10 seconds
Emitting frequency	433MHz/868MHz
Receiving distance	>200m（open area）
Sensitivity	≥104dB
Emitting power	12±1dB
Zone delay	3200 ms
Alarm output switch contain	24V/0.5A
Alarm dialing mode	DTMF
DTMF dialing frequency tolerance	< 1.5 %
CMS connection protocol	Ademco Contact ID
Environment	5 ℃～45 ℃
Humidity	< 85 %



DSM-824

◎
◎
◎

◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎
◎

Value applying at rated voltage

The information contained herein os believed to be correct,but no guarantee for accuracy ,completeness
DSW electronics LTD.reseves the right to make changes without notification